


STACKING P-PL 30 - INDOOR

David Rockwell, 2025



Discover more



REPLACEABLE LED

| TECHNICAL SHEET  |                                                                                                                                |
|------------------|--------------------------------------------------------------------------------------------------------------------------------|
| TYPE             | Wall/Ceiling                                                                                                                   |
| MATERIALS        | Diffuser: Blown Borosilicate Glass<br>Structure: Anodized or painted aluminum                                                  |
| DIMENSIONS       | Diffuser: [Ø4" H12 5/8"] Ø10cm H32cm<br>Depth: [5 1/2"] 14cm                                                                   |
| LIGHT SOURCE     | 5 X LED STRIP 24V 6,25W (total) 718 lm (nominal) 3000K CRI≥90<br>5 X LED STRIP 24V 6,25W (total) 687 lm (nominal) 2700K CRI≥90 |
| DIMMING PROTOCOL | 0/1-10V; Phase cut                                                                                                             |
| MARKING          | DRY LOCATION                                                                                                                   |
| NET WEIGHT       | 4 lbs                                                                                                                          |
| NOTE:            | Can be installed vertically and horizontally                                                                                   |

|                |  |
|----------------|--|
| PROJECT NAME   |  |
| SPECIFIER NAME |  |

We reserve the right to change our product specifications.  
Please visit [www.leucos.com](http://www.leucos.com) for the latest product information

North America

LEUCOS



|                                               |                        |                    |     |      |
|-----------------------------------------------|------------------------|--------------------|-----|------|
| DIMMING PROTOCOL                              | 0/1-10V; Phase cut     |                    |     |      |
| FINISH (DIFFUSER + STRUCTURE)                 | SOURCE                 | CODE               | QTY | TYPE |
| Transparent + Anodized Aluminum               | LED 3000K<br>LED 2700K | 0014033<br>0014034 |     |      |
| Transparent + Matte Black Aluminum            | LED 3000K<br>LED 2700K | 0014075<br>0014074 |     |      |
| **Metallic Petrol Blue + Anodized Aluminum    | LED 3000K<br>LED 2700K | 0014240<br>0014241 |     |      |
| **Metallic Petrol Blue + Matte Black Aluminum | LED 3000K<br>LED 2700K | 0014242<br>0014243 |     |      |
| **Metallic Titanium + Anodized Aluminum       | LED 3000K<br>LED 2700K | 0014244<br>0014245 |     |      |
| **Metallic Titanium + Matte Black Aluminum    | LED 3000K<br>LED 2700K | 0014246<br>0014247 |     |      |

\*\*ON REQUEST: PVD METALIZED TREATMENT

MINIMUM ORDER QUANTITY 8 PCS PER COLOR