


STACKING P-PL 30 MLR VU

David Rockwell, 2025



TECHNICAL SHEET	
MATERIALS	Diffuser: Millerighe Borosilicate Glass Structure: Aluminum
	Diffuser: [Ø4" H12 5/8"] Ø10cm H32cm Depth: [5 1/2"] 14cm
LIGHT SOURCE	5 X LED STRIP 24V 6,25W (total) 718lm (nominal) 3000K CRI≥90 5 X LED STRIP 24V 6,25W (total) 687lm (nominal) 2700K CRI≥90
DIMMING PROTOCOL	0/1-10V, Phase Cut
MARKING	DRY LOCATION
NET WEIGHT	4,4 lbs 
NOTE	Can be installed vertically and horizontally

PROJECT NAME	
SPECIFIER NAME	

We reserve the right to change our product specifications.
Please visit www.leucos.com for the latest product information

HQ: 6 Kilmer Rd Suite B - Edison, NJ 08817, US
WH: 2351 Us Highway 130 Ste B - Dayton, NJ 08810-1648, US

North America

LEUCOS



DIMMING PROTOCOL	0/1-10V; Phase cut			
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE	QTY	TYPE
Transparent Millerighe + Anodized Aluminum	LED 3000K	0014041		
	LED 2700K	0014042		
Transparent Millerighe + Matte Black Aluminum	LED 3000K	0014083		
	LED 2700K	0014082		
Amber Millerighe + Anodized Aluminum	LED 3000K	0014041/MA		
	LED 2700K	0014042/MA		
Amber Millerighe + Matte Black Aluminum	LED 3000K	0014083/MA		
	LED 2700K	0014082/MA		

<https://www.leucos.com/en-us/>
info.us@leucos.com

Tel +1 (732) 225-0010